

---

**Manual sealless steel strapping tool**

---



---

**Characteristics**

---

|                        |  |
|------------------------|--|
| Strapping qualities:   | Uniflex regular duty max. 850 N/mm <sup>2</sup> / 123'000 psi                    |
| Strapping dimensions:  | widths 9.5 – 13.0 mm / <sup>3</sup> / <sub>8</sub> – ½"                          |
|                        | thicknesses 0.38 – 0.50 mm / .015 – .020"  |
| Weights:               | 3.3 kg / 7.3 lbs Normal version<br>3.7 kg / 8.1 lbs TW version                   |
| Average seal strength: | approx. 80 %   |
| TW-version available:  | Torque wrench tensioning system  |
| Suspension (Optional): | Bolt and grip ball for horizontal applications;<br>have to be ordered separately |

---

**Advantages**

---

- Handy light weight sealless combination tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals
- Thanks to its weight of 3.3 kg / 7.3 lbs only, it is very suitable for horizontal applications

## Chart of types model A332 and A332/TW

| Item No. | Model                  | Uniflex<br>max. 850 N/mm <sup>2</sup> / 123'000 psi |      |             |           |
|----------|------------------------|---|------|-------------|-----------|
|          |                        | Width   |      | Thicknesses |           |
|          |                        | mm  | inch | mm          | inch      |
| 13.2250  | A332/9.5/0.38-0.50     | 9.5   | 3/8" | 0.38-0.50   | .015-.020 |
| 13.2260  | A332/10/0.38-0.50      | 10.0  |      | 0.38-0.50   | .015-.020 |
| 13.2270  | A332/12.7/0.38-0.50    | 12.7  | 1/2" | 0.38-0.50   | .015-.020 |
| 13.2280  | A332/13/0.38-0.50      | 13.0  |      | 0.38-0.50   | .015-.020 |
| 13.2251  | A332/9.5/0.38-0.50/TW  | 9.5   | 3/8" | 0.38-0.50   | .015-.020 |
| 13.2261  | A332/10/0.38-0.50/TW   | 10.0  |      | 0.38-0.50   | .015-.020 |
| 13.2271  | A332/12.7/0.38-0.50/TW | 12.7  | 1/2" | 0.38-0.50   | .015-.020 |
| 13.2281  | A332/13/0.38-0.50/TW   | 13.0  |      | 0.38-0.50   | .015-.020 |

TW = Torque wrench tensioning system

## Accessories

- A33.4101 Bolt for horizontal applications  
(in combination with grip ball N4. 1116)
- N4.1116 Grip ball for horizontal applications  
(in combination with bolt A33.4101)
- A33.0113 Suspension for vertical applications