

Manual sealless steel strapping tool for high tensi on



Characteristics

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi	
Strapping dimensions:	widths	12.7 – 19.0 mm / ½ – ¾"
	thicknesses	0.50 – 0.70 mm / .020 – .028"
Weights:	5.7 kg / 12.6 lbs Normal-version	
	5.9 kg / 13.0 lbs TW-version	
Average seal strength:	approx. 80 %	
Versions available:	Torque wrench tensioning system MicroLock™ system	
Suspension (Optional):	Suspension for vertical and horizontal applications; has to be ordered separately	
	Handle for horizontal applications; has to be ordered separately	

Advantages

- The special tensioning gear-system allows a high strap tension of up to 5500 N (1240 lbs) with a limited amount of tensioning effort of only 240 N (54 lbs)
- Handy sealless combination tool to strap flat packages (e.g. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals
- The MicroLock™ sealless system guarantees a maximum of security of the sealless steel strapping joint against unlocking

Chart of types model A338

Item No.	Model	Width		Uniflex Thicknesses		Ultraflex Thicknesses	
		mm	inch	mm	inch	mm	inch
13.2910	A338/12.7/0.50-0.64	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2911	A338/12.7/0.50-0.64/TW	12.7	1/2"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2915	A338/12.7/0.70/UNI	12.7	1/2"	0.70	.028	-	-
13.2916	A338/12.7/0.70/UNI/TW	12.7	1/2"	0.70	.028	-	-
13.2920	A338/13/0.50-0.64	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2921	A338/13/0.50-0.64/TW	13		0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2925	A338/13/0.70/UNI	13		0.70	.028	-	-
13.2926	A338/13/0.70/UNI/TW	13		0.70	.028	-	-
13.2930	A338/16/0.50-0.64	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2931	A338/16/0.50-0.64/TW	16	5/8"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2935	A338/16/0.70/UNI	16	5/8"	0.70	.028	-	-
13.2936	A338/16/0.70/UNI/TW	16	5/8"	0.70	.028	-	-
13.2940	A338/19/0.50-0.64	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2941	A338/19/0.50-0.64/TW	19	3/4"	0.50-0.64	.020-.025	0.50-0.64	.020-.025
13.2945	A338/19/0.70/UNI	19	3/4"	0.70	.028	-	-
13.2946	A338/19/0.70/UNI/TW	19	3/4"	0.70	.028	-	-

Uniflex = Regular duty strapping max. 850 N/mm² / 12000'3 psi
 Ultraflex = High tensile strapping max. 1100 N/mm² / 0'16000 psi
 TW = Torque wrench tensioning system



مؤسسة فصول الخليج لمعدات وأدوات التغليف
 GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740
 Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061
 Jeddah Branch: Tel: +966 (12) 608 4832, Fax: +966 (12) 608 4835
 Website: www.gspackaging.net
 E-mail: sales@gspackaging.net, info@gspackaging.net

w

Chart of types model A338 with MicroLock™

Item No.	Model	Width		Uniflex Thicknesses		Ultraflex Thicknesses	
		mm	inch	mm	inch	mm	inch
13.2950	A0.64-0.50/12.7/338/ML	12.7	2/1"	0.64-0.50	.025-.020	0.64-0.50	.025-.020
13.2951	A0.64-0.50/12.7/338/ML /TW	0-0.50	"2/1	12.7	.025-.020.	0.64-0.50	025-.020. 64
13.2955	A0.70/12.7/338/UNI/ML	12.7	2/1"	0.70	.028	-	-
13.2956	A0.70/12.7/338/UNI/ML /TW	0.	0.70	"2/1	12.7 28	-	-
13.2960	A0.64-0.50/13/338/ML	13		0.64-0.50	.025-.020	0.64-0.50	.025-.020
13.2961	A0.64-0.50/13/338/ML /TW	020.	0.64-0.50		13 -.025-.020.	0.64-0.50	025
13.2965	A0.70/13/338/UNI/ML	13		0.70	.028	-	-
13.2966	A0.70/13/338/UNI/ML /TW	028.	0.70		13	-	-
13.2970	A0.64-0.50/16/338/ML	16	8/5"	0.64-0.50	.025-.020	0.64-0.50	.025-.020
13.2971	A0.64-0.50/16/338/ML /TW	0.64-0.50	"8/5	16	.025-.020.	0.64-0.50	025-.020
13.2975	A0.70/16/338/UNI/ML	16	8/5"	0.70	.028	-	-
13.2976	A0.70/16/338/UNI/ML /TW	028.	0.70	"8/5	16	-	-
13.2980	A0.64-0.50/19/338/ML	19	4/3"	0.64-0.50	.025-.020	0.64-0.50	.025-.020
13.2981	A0.64-0.50/19/338/ML /TW	0.64-0.50	"4/3	19	.025-.020.	0.64-0.50	025-.020
13.2985	A0.70/19/338/UNI/ML	19	4/3"	0.70	.028	-	-
13.2986	A0.70/19/338/UNI/ML /TW	028.	0.70	"4/3	19	-	-

Uniflex = Regular duty strapping max. 850 N/mm² / 000'123 psi
 Ultraflex = High tensile strapping max. 1100 N/mm² / 000'160 psi
 TW = Torque wrench tensioning system
 ML= MicroLock™

Accessories

- A33.5301 Suspension for vertical and horizontal applications
- A33.5307 Handle for horizontal applications



مؤسسة فصول الخليج لمعدات وأدوات التغليف
 GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740
 Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061
 Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167
 Website: www.gspackaging.net
 E-mail: sales@gspackaging.net, info@gspackaging.net