

## Pneumatic pusher type combination steel strapping tool



## Characteristics

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm <sup>2</sup> / 160'000 psi
Strapping dimensions:	widths 25.0 and 32.0 mm / 1 and 1 ¼"
	thicknesses 0.80 – 1.00 mm / .031-.040"
Weights:	18.0 kg / 39.7 lbs without suspension 19.5 kg / 43.0 lbs with suspension
Average seal strength:	approx. 75 %
Seals:	Overlap seals, see chart
Type of joint:	Double notch upcut joint
Strap tension:	The tool is available for two different stages for strap tension, see charts
Suspension:	Four different suspension brackets are available; have to be ordered separately, see accessories

## Advantages

- The most rugged pusher type strapping tool of its kind for continuous and shift operations demanding a high working reliability
- High performance machine with an outstanding record of performance in the steel and non ferrous industries
- The perfect double notch upcut seal joint is accomplished in one operation
- Inserting of the strap into the tools is easy since the feed wheel is lifted pneumatically and no operator effort is required
- Four different suspension brackets are available thus allowing the tool to be mounted in any possible suspension position

## Chart of types model A483

Item No	Model	Width		Thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/s	inch/s
13.4730	A483/25/0.80-1.00/7.0/UNI	25	1"	0.80-1.00	.031-.040	7000	1570	200	8.0
13.4710	A483/25/0.80-0.90/7.0/ULT	25	1"	0.80-0.90	.031-.035	7000	1570	200	8.0
13.4770	A483/32/0.80-1.00/7.0/UNI	32	1 ¼"	0.80-1.00	.031-.040	7000	1570	200	8.0
13.4780	A483/32/0.80-1.00/9.0/UNI	32	1 ¼"	0.80-1.00	.031-.040	9000	2020	160	6.5
13.4750	A483/32/0.80-0.90/7.0/ULT	32	1 ¼"	0.80-0.90	.031-.035	7000	1570	200	8.0
13.4760	A483/32/0.80-0.90/9.0/ULT	32	1 ¼"	0.80-0.90	.031-.035	9000	2020	160	6.5

UNI = Uniflex regular duty strapping max. 850 N/mm<sup>2</sup> / 12000'3 psi  
 ULT = Ultraflex high tensile strapping max. 1100 N/mm<sup>2</sup> / 0'16000 psi

## Accessories

		S trapping position		
		normal	vertical	horizontal
A48.3401	Suspension bracket normal	*	*	*
A48.3406	Suspension bracket front	⊙	*	⊙
A48.3413	Suspension bracket lateral	⊙	⊙	*
A48.3419	Suspension bracket universal (with integrated air supply)	⊙	⊙	⊙

\* = changing of the suspension position possible by moving the cable hook

⊙ = changing of the suspension position without moving the cable hook (very fast changes possible, perfect for frequent changes)

## Recommended seals

Width mm	Inch	Dimensions (W, L, T)	
		mm	inch
25	1"	25 x 45 x 0.9	1 x 1 ¾ x .035
32	1 ¼"	32 x 45 x 0.9	1 ¼ x 1 ¾ x .035

Tensile strength of the seal material: 600 N/mm<sup>2</sup> / 87'000 psi



مؤسسة فصول الخليج لمعدات وأدوات التغليف  
 GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740  
 Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061  
 Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167  
 Website: www.gspackaging.net  
 E-mail: sales@gspackaging.net, info@gspackaging.net