

The semi-automatic solution with top price/performance ratio



Characteristics

Ring diameters:	50 cm	90 cm	120 cm	160 cm	200/200 cm
Standard film quality:	23 mμ	23 mμ	23 mμ	23 mμ	23 mμ
Film reel dimensions:	100 mm	170, 100 mm	170, 100, 200 mm	170, 100, 200 mm	170, 100, 200 mm
Max. ring speed:	300 rpm	140 rpm	70 rpm	60 rpm	50 rpm
Power supply:	230 V	230 V	230 V	230 V	230 V
Power consumption:	0,26 Kw	0,31 Kw	0,48 Kw	0,52 Kw	0,50 Kw
Inverter / PLC:	Omron	Omron	Fuji / Omron	Fuji / Omron	Fuji / Omron

Advantages

- CE certified
- Proven quality with competitive price
- Easy operation, simple maintenance
- In various inner ring diameters available
- Double film reel dispenser
- Safety foot switch
- Ring protection
- Adjustable stretch film tension
- Adjustable ring speed
- Various optional features, i.e.
 - Automatic film cutter
 - Top press

Chart of types model FV٣٠٠

Item No.	Model	Inner diameter
31.3001	FV50/300	50 cm
31.3002	FV90/300	90 cm
31.3003	FV125/300	125 cm
31.3004	FV160/300	160 cm
31.3005	FV200/300	200 cm
31.3006	FV250/300	250 cm



مؤسسة فصول الخليج لمعدات وأدوات التغليف
GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740
Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061
Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167
Website: www.gspackaging.net
E-mail: sales@gspackaging.net, info@gspackaging.net