

## Manual plastic strapping tools

---



### Characteristics

---

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths	11.0 – 13.0 mm / ½"
	thicknesses	0.40 – 0.90 mm / .016 - .035"
Weights:		3.3 kg / 7.3 lbs without suspension
		3.4 kg / 7.5 lbs with suspension
Average seal strength:		approx. 70 %
Type of joint:		Joint with special seals
Suspension (Optional):		bolt and grip ball for horizontal applications; have to be ordered separately

### Advantages

---

- Handy light weight tensioning and sealing tool to strap flat packages (i.e. pallets, barrels, crates, cases, various packages) using plastic strapping
- A reliable, robust and service-friendly tool
- The windless tensioning system allows very high strap tension
- Special serrated seals and the patented sealing force balance system guarantee a very high seal joint efficiency
- The sealing handle is always operated until it hits the stop – thus the seal efficiency of all joints is high and balanced

## Chart of types model P403

Item No.	Model	Width		Thicknesses	
		mm	inch	mm	inch
43.0403	P403/11-13/0.40-0.90	11-13	½"	0.40-0.90	.016-.035

## Seals

Item No.	Model	Width		Contents of carton in pcs.	Weight	
		mm	inch		kg	lbs
41.5081	P403/13	11-13	½"	1000	6.5	14.3

## Accessories

P40.2046 Handle for horizontal applications  
(Grip ball and bolt)

**GS PACKAGING**مؤسسة فصول الخليج لمعدات وأدوات التغليف  
GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740  
Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061  
Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167  
Website: www.gspackaging.net  
E-mail: sales@gspackaging.net, info@gspackaging.net