

The most economical solution for every budget

---



### Characteristics

---

Strapping qualities:	Polypropylene (PP)	
Strapping dimensions:	widths	6.0 – 15.5 mm
	thicknesses	0.5 – 0.75 mm
Strapping tension:	adjustable, 150 – 450 N	
Sealing method:	heat welding	
Power supply:	230V / 50Hz, 1 phase	
Power consumption:	0.25 kWh	
Strapping speed:	2.5 sec./cycle (approx. 24 strapping cycles/min.)	
Dimensions:	length	902 mm
	width	586 mm
	table height	760-930 mm adjustable
Weight:	85 kg	
Max. package weight	100 kg	
Min. package size:	80W x 20H mm	
Strap core inner diameter:	200 / 230 / 280 mm (interchangeable)	
Temp. of working environment:	5 ~ 40°C	

### Advantages

---

- Light, compact design
- Easy operation, simple maintenance
- CE certified
- Hinged stainless top plate
- Mechanical outside tension control
- Rigid castors with brake
- Automatic motor stop to save energy
- Reliable P.C. board electric control
- Adjustable table height from 760 to 930 mm
- Affordable for every budget, total value more than competing brands
- Proven quality
- Interchangeable strap core inner diameter from 200 mm to 280 mm
- Safety limit switch included

### Chart of types model PM206

---

Item No.	Model
44.2020	PM206



مؤسسة فصول الخليج لمعدات وأدوات التغليف  
GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740  
Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061  
Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167  
Website: www.gspackaging.net  
E-mail: sales@gspackaging.net, info@gspackaging.net