

The new generation machine enhanced model

---



### Characteristics

---

Strapping qualities:	Polypropylene (PP)	
Strapping dimensions:	widths	5.0 – 13.0 mm
	thicknesses	0.45 – 0.65 mm
Strapping tension:	adjustable, 80 – 450 N	
Sealing method:	heat welding	
Power supply:	230V / 50Hz, 1 phase	
Power consumption:	0.3 kWh	
Strapping speed:	2.5 sec./cycle (approx. 24 strapping cycles/min.)	
Dimensions:	length	850 mm
	width	560 mm
	table height	780-950 mm adjustable
Weight:	70 kg	
Max. package weight	80 kg	
Min. package size:	80W x 20H mm	
Strap core inner diameter:	200 / 230 / 280 mm (interchangeable)	
Temp. of working environment:	5 ~ 40°C	

### Advantages

---

- Light, compact design
- Easy operation, simple maintenance
- CE certified
- Compact mechanical control head with 30 % less moving parts
- Hinged stainless top plate
- Electronic outside tension control
- Sensor controlled heater
- Rigid castors with brake
- Automatic motor stop to save energy
- Reliable P.C. board electric control
- Adjustable table height from 780 to 950 mm
- Proven quality
- Interchangeable strap core inner diameter from 200 mm to 280 mm
- Safety limit switch included

### Chart of types model PM207

---

Item No.	Model
44.2050	PM207



مؤسسة فصول الخليج لمعدات وأدوات التغليف  
GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740  
Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061  
Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167  
Website: [www.gspackaging.net](http://www.gspackaging.net)  
E-mail: [sales@gspackaging.net](mailto:sales@gspackaging.net), [info@gspackaging.net](mailto:info@gspackaging.net)