

The enhanced machine model for wide strapping



Characteristics

| | | |
|-------------------------------|---|----------------|
| Strapping qualities: | Polypropylene (PP) | |
| Strapping dimensions: | widths | 8.0 – 12.0 mm |
| | thicknesses | 0.55 – 0.75 mm |
| Strapping tension: | adjustable, 70 – 700 N | |
| Sealing method: | heat welding | |
| Power supply: | 230V / 50Hz, 1 phase | |
| Power consumption: | 1.2 kWh | |
| Strapping speed: | 2.1 sec./cycle (approx. 29 strapping cycles/min.) | |
| Dimensions: | length | 1430 mm |
| | width | 620 mm |
| | table height | 810 mm |
| Machine net weight: | 220 kg | |
| Max. package weight: | 100 kg | |
| Min. package size: | 130W x 20H mm | |
| Arch size: | 850 x 600 mm standard | |
| Temp. of working environment: | 5 ~ 40°C | |

Advantages

- Proven quality
- Competitive price
- CE certified
- Bundles and cartons can be strapped very easily and quickly
- User-friendly and easy strapping coil change
- Easy operation, simple maintenance
- Electronic outside tension control
- Tension can be easily set with a dial
- Mobile, on wheels with brakes
- Auto strap reefed
- Strap end ejector
- Short feed sensor and foot switch included

Chart of types model PM309

| Item No. | Arch size W x H (mm) | Strap width | Colour |
|----------|-------------------------|----------------|--------|
| 45.4111 | 650 x 400 | 9.00 mm | blue |
| 45.4112 | 650 x 400 | 12.0 mm | blue |
| 45.4121 | 850 x 600 | 9.0 mm | blue |
| 45.4122* | 850 x 600 | 12.0 mm | blue |
| 45.4131 | 1050 x 800 | 9.0 mm | blue |
| 45.4132* | 1050 x 800 | 12.0 mm | blue |
| 45.4141 | 1250 x 1000 | 9.0 mm | blue |
| 45.4142 | 1250 x 1000 | 12.0 mm | blue |

* Machines in stock, NL-Nieuwegein.
Availability other machines upon request.
Different arch sizes possible.



مؤسسة فصول الخليج لمعدات وأدوات التغليف
GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740
Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061
Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167
Website: www.gspackaging.net
E-mail: sales@gspackaging.net, info@gspackaging.net