

# **MH600**

**High tension PET friction weld  
strapping head**

# MH600

## All electric high tension PET friction weld strapping head

The MH600 strapping head has been designed for automatic, heavy duty industrial PET strapping installations. The head processes strapping from 13 - 19 mm (1/2 - 3/4") of various thicknesses and qualities. The high strap tension feature (up to 7000 N / 1545 lbs) allows applications of PET strapping with break strengths up to 15000N (3300 lbs).

### Features



- Compact and modular design
- One piece of aluminum cast housing
- High strap tension up to 7000N (1545 lbs), electronically adjustable
- Wide strap width range without changing parts
- Strap guide open feature
- Well proven separate feeding, tensioning and friction weld sealing systems
- High consistent seal efficiency because of environment temperature monitoring
- Long life and maintenance friendly, resulting in high availability
- 3 side suspension point for easy integration

### Technical Data

Strapping Widths: 13 - 19 mm / 1/2 - 3/4"  
 Thicknesses: 0.64 - 1.53 mm / 0.025 - 0.060"  
 Quality: PET  
 Pack width: min. 250 mm / 10"  
 Seal joint: Friction weld  
 Seal efficiency: up to 80%  
 Strap tension: 2500N / 7000N adjustable  
 (560 lbs / 1570 lbs )  
 Feed/retract speed: 5.3 m/s / 17.3 ft./s  
 Tension speed: 105 mm/s / 0.34 ft./s  
 Power supply: 230V - 3PE /50Hz  
 Consumption: 1.1KW  
 Control voltage: 24V DC  
 Weight: 115 kg / 253 lbs

### Options

- Headsuspension with power floating system
- Mechanical pack height sensor
- Thinner or rubber coated base protection plate
- S trap guide arch systems
- S trap dispensers
- Control
- Complete custom built strapping machines
- Dust cleaning system
- Counter



مؤسسة فصول الخليج لمعدات وأدوات التغليف  
 GULF SEASON STRAPPING & PACKAGING SYSTEMS

Dammam Head Office: Tel: +966 (13) 847 3734 / 847 3735, Fax: +966 (13) 847 3740  
 Riyadh Branch: Tel: +966 (11) 438 9060, Fax: +966 (11) 438 9061  
 Jeddah Branch: Tel: +966 (12) 602 0241, Fax: +966 (12) 602 0167  
 Website: www.gspackaging.net  
 E-mail: sales@gspackaging.net, info@gspackaging.net